

XW272K

Multifunction split controller for medium and low temperature ventilated applica

K: OS open board (or in OA, GS, PS format)

Features

Display	On keyboard 3 digits, d.p., -
Remote keyboard	6 push buttons (T620-V620)
Power supply	110, 230Vac

Probe inputs

Thermostat	NTC
Defrost	NTC
Display	NTC

Digital inputs

Alarm, block alarm, pressure switch, start defrost, energy saving, ON/OFF AUX, holiday	configurable
Door switch	present

Relay outputs

Compressor	20A
2nd compressor	20A
Defrost	8A
Fans	8A
Light	16A 16A neon optional
Alarm	8A

Other Outputs


Hot Key/Prog Tool Kit output	present
Serial output	TTL, RS485 optional
Analog output	4÷20mA optional

Other

Buzzer	On keyboard optional
---------------	----------------------

Measurement

Measurement range	Probe dependent
--------------------------	-----------------



Accuracy	Better than 1% of full scale
-----------------	------------------------------

Generals

Data Storage	EEPROM memory
---------------------	---------------

Operating temperature	0°÷60°C 32°÷140°F
------------------------------	----------------------

Storage temperature	-30°÷85°C 22°÷185°F
----------------------------	------------------------

Relative humidity	20÷85%
--------------------------	--------

Resolution	0.1°C or 1°F
-------------------	--------------