

IC111L

Advanced multifunction controller for chiller/heat pump with 1 circuit and 1 com L: 38x185mm, panel mounting

Features

First display	3 digits, d.p., -
Second display	4 digits, d.p., -
Keyboard	6 push buttons
Power supply	12Vac/dc, 24Vac/dc optional 110, 230Vac

Probe inputs

Pb1	NTC - configurable
Pb2	NTC - configurable
Pb3	NTC/4÷20mA configurable
Pb4	NTC/dig inp configurable

Digital inputs

Low pressure switch	present
High pressure switch	present
N° Digital inputs	4 configurable

Relay outputs

RL1 Compressor 1	8A
RL2	8A configurable
RL3	8A configurable
RL4	8A configurable
RL5	8A configurable optional

Other Outputs

Hot Key/Prog Tool Kit output	present
Remote keyboard output	present (for VI610)
Serial output	TTL
Alarm output	12Vdc - 40mA max
Analog output	4÷20mA for fan speed module-optional
Signal output for triac or on/off fan module	PWM

Other



Buzzer	optional
---------------	----------

Real time clock	optional
------------------------	----------

Measurement

Measurement range	Pressure probe: 0÷50bar NTC probe: -40÷110°C (-40÷230°F)
--------------------------	--

Accuracy	±0.7°C ±1digit
-----------------	----------------

Generals

Housing	Self extinguishing ABS
----------------	------------------------

Front protection	IP 65 with gasket
-------------------------	-------------------

Power absorption	5VA max
-------------------------	---------

Display type	1st: red LED (8.0mm high) 2nd: yellow LED (5.6mm high)
---------------------	---

Data Storage	EEPROM memory
---------------------	---------------

Operating temperature	-10°÷60°C 14°÷140°F
------------------------------	------------------------

Storage temperature	-30°÷85°C -22°÷185°F
----------------------------	-------------------------

Relative humidity	20÷85% (non condensing)
--------------------------	-------------------------

Resolution	0.1°C or 1°F (selectable)
-------------------	---------------------------

Connection	Disconnectable connectors (12-14 pin or 14-6 pin or 16-8 pin)
-------------------	---