

IC281D

Advanced multifunction controllers for chiller with heat pump and chillers with D: 10 DIN Rail mounting

Features

First display	On keyboard 3 digits, d.p., -
Second display	On keyboard 4 digits, d.p., -
Power supply	12Vac/dc, 24Vac/dc optional

Probe inputs

All Probes	NTC/PTC/4÷20mA/0÷5V 10 configurable
-------------------	--

Digital inputs

N° Digital inputs	18 configurable
--------------------------	-----------------

Relay outputs

N° relay outputs	14 of 5A
-------------------------	----------

Other Outputs

Hot Key/Prog Tool Kit output	present
Remote keyboard output	VI820 (up to 2)
Serial output	TTL, RS485
PWM outputs for condensing fan	2
0÷10V or 4÷20mA outputs for condensing fan	2 configurable
0÷10V outputs for free cooling, heat recovery, external relay	4 configurable

Other

Buzzer	optional
Real time clock	optional

Measurement

Measurement range	Pressure probe: 0÷50bar NTC probe: -30÷70°C (-22÷158°F) PTC probe: 0÷150°C (32÷302°F)
Accuracy	±0.7°C ±1digit



Generals

Housing	Self extinguishing ABS
Power absorption	10VA max
Data Storage	EEPROM memory
Operating temperature	-10°÷60°C 14°÷140°F
Storage temperature	-30°÷85°C -22°÷185°F
Relative humidity	20÷85% (non condensing)
Resolution	0.1°C or 1°F (selectable)
Connection	Disconnectable connectors (12-14 pin or 14-6 pin or 16-8 pin)