

IPG115D

General purposes programmable controller with 15 relay outputs

D: 10 DIN Rail mounting

Features

Power supply	24Vac/dc (from TF20D)
---------------------	-----------------------

Probe inputs

0÷1V - 0÷5V - 0÷10V - 2÷20mA - 4÷20mA - NTC - PTC - DI	10 configurable
--	-----------------

Digital inputs

Opto-insulated	20 configurable
-----------------------	-----------------

Relay outputs

Configurable Relay Outputs	12x5A +3x8A
-----------------------------------	-------------

Other Outputs

Remote display output	present, up to 3 (for VGIPD)
Remote keyboard output	VGIPG (up to 2)
PWM outputs for fan speed module	2
0÷10V or 4÷20mA outputs for fan speed module	2 configurable
0÷10V or external relay analog output	4 configurable
Master serial output	RS485
Slave serial output	RS485
USB	present
Modem output	GSM, XWEB Modem - optional
CAN Bus output	present
Ethernet enabled	optional

Other

Buzzer	present
Real time clock	present
Expansion module	IPEX60D
Internal modem	optional



Measurement

Measurement range	Pressure probe: 0÷50bar NTC probe: -40÷110°C (-40÷230°F) PTC probe: -40÷150°C (-40÷302°F)
Accuracy	±0.7°C ±1digit

Generals

Housing	Self extinguishing ABS
Power absorption	20VA max
Data Storage	EEPROM memory
Operating temperature	-10°÷60°C 14°÷140°F
Storage temperature	-30°÷85°C -22°÷185°F
Relative humidity	20÷85% (non condensing)
Resolution	0.1°C or 1°F (selectable)
Connection	Disconnectable connectors